

SPECIFICATIONS

INVO Switchable LED SKY Panel

Introducing our new multi wattage and CCT switchable INVO LED SKY Panel. Simple dip switches on the driver allow you to choose the wattage (25/35/40/50W) and CCT (3000k/4000K/5000K). A sleek, versatile and easy to fit solution either within a grid system or on a solid ceiling using a mounting kit. This panel offers a stable lumen efficiency of 160 Lumens per Watt. The very efficient LED means you can use a far lower powered LED fitting to produce equal, if not better, light levels than those already in place, coupled with our market leading 5 year warranty, you get peace of mind, fantastic lighting and incredible paybacks.

- > CCT Switchable 3000k/4000k/5000k
- Selectable wattage output 26/30/35/40W
- > 5 Year warranty
- Available in standard, Emergency and Sensor versions
- > Flicker free driver
- > 160 Lumen per watt
- High quality PC diffuser (perfect uniformity)



Specification	INVO Switchable LED SKY Panel			
Wattage	26	30	35	40
Lumen Output	4160 Lumen	4800 Lumen	5600 Lumen	6400 Lumen
CCT	3000k/4000k/5000k			
Dimension (mm)	595mm × 595mm × 10mm			
Beam Angle	160 degrees			
Emergency backup	Optional			
Microwave sensor	Optional			

